

# Asbestos Packing with Graphite Impregnation

Code: KXTP806



## Description

Braided from high quality asbestos fiber impregnated with graphite and oil, it has good elasticity and good sliding properties. It can be reinforced with metal wire.

**KXT-P806S** -- Glass Fiber Packing reinforced with SS Wire



Item no.: KXTP806

Asbestos Packing with Graphite Impregnation  
Item no.: KXTP806

- \* Low maintenance, easy to control
- \* Excellent capabilities of high strength and high temperature resistance
- \* Economical packing

## Typical Application

- \* Universal packing, for rotary, reciprocating pumps, in ship building and domestic fresh water pumps.
- \* Suited for chemical neutral and resistant to water, steam, hot air, oils, etc.

## Technical Data

Material		Asbestos Fiber and Graphite
Temperature Range		-100 up to +450 oC
Process	Rotating	20 bar
	Reciprocating	40 bar
	Static	80 bar
Shaft Speed		10 m/s
PH		3~12
Density		0.75~1.5 g/cm3

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,

Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:[sales@seal-china.com](mailto:sales@seal-china.com)